

**SECTION 1: Identification**

**1.1. Identification**

Product form : Mixture  
Product name : Poxylube #800 PTFE Coating - Heat Curing - Clear  
Product code : E800-C01

**1.2. Recommended use and restrictions on use**

Recommended use : Epoxy  
Restrictions on use : Food/feedstuff additives

**1.3. Supplier**

Sandstrom Products Company  
224 S Main St  
Port Byron, IL 61275  
USA  
T 309-523-2121 - F 309-230-9745

**1.4. Emergency telephone number**

Emergency number : CHEMTREC (800) 424-9300 | (703) 527-3887

**SECTION 2: Hazard(s) identification**

**2.1. Classification of the substance or mixture**

**GHS US classification**

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Germ cell mutagenicity Category 1B	H340	May cause genetic defects
Carcinogenicity Category 1B	H350	May cause cancer
Reproductive toxicity Category 2	H361	Suspected of damaging fertility or the unborn child
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

**2.2. GHS Label elements, including precautionary statements**

**GHS US labeling**

Hazard pictograms (GHS US) :





Signal word (GHS US) : Danger  
Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H340 - May cause genetic defects  
H350 - May cause cancer

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Precautionary statements (GHS US)

H361 - Suspected of damaging fertility or the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call a poison center or doctor if you feel unwell.  
P314 - Get medical advice/attention if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

56.97% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
79.88% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
81.88% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Methyl Ethyl Ketone	CAS-No.: 78-93-3	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Propylene Glycol Methyl Ether	CAS-No.: 107-98-2	15 – 25	Flam. Liq. 3, H226 STOT SE 3, H336
toluene	CAS-No.: 108-88-3	15 – 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
1-butanol	CAS-No.: 71-36-3	1 – 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
Stoddard solvent	CAS-No.: 8052-41-3	0.1 – 0.5	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Wear respiratory protection.

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Color : clear  
Odor : strong Solvent  
Odor threshold : No data available  
pH : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : 52 °F  
Relative evaporation rate (butyl acetate=1) : No data available  
Flammability (solid, gas) : Not applicable.  
Vapor pressure : No data available  
Relative vapor density at 20°C : No data available  
Relative density : 0.909 lb/gal  
Density : 7.84 lb/gal  
Solubility : No data available  
Partition coefficient n-octanol/water (Log Pow) : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Viscosity, kinematic : 15 – 25 SEC, 2 ZAHN  
Viscosity, dynamic : No data available  
Explosion limits : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 9.2. Other information

VOC content : 5.86 lb/gal

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

### Poxylube #800 PTFE Coating - Heat Curing - Clear

Unknown acute toxicity (GHS US)	56.97% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 79.88% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 81.88% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
---------------------------------	--

### Propylene Glycol Methyl Ether (107-98-2)

LD50 oral rat	4016 mg/kg body weight (EU Method B.1 tris: Acute oral toxic – Acute toxic class method, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (Equivalent or similar to EU Method B.3, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA
ATE US (oral)	4016 mg/kg body weight

### 1-butanol (71-36-3)

LD50 oral rat	2292 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	3430 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>1-butanol (71-36-3)</b>	
LC50 Inhalation - Rat	> 17.76 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	2292 mg/kg body weight
ATE US (dermal)	3430 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
<b>toluene (108-88-3)</b>	
IARC group	3 - Not classifiable
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
<b>Methyl Ethyl Ketone (78-93-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>toluene (108-88-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Propylene Glycol Methyl Ether (107-98-2)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>1-butanol (71-36-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
<b>toluene (108-88-3)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Propylene Glycol Methyl Ether (107-98-2)</b>	
LOAEL (oral,rat,90 days)	2757 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (oral,rat,90 days)	919 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	> 1000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
<b>Stoddard solvent (8052-41-3)</b>	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: 15 – 25 SEC, 2 ZAHN
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

##### Propylene Glycol Methyl Ether (107-98-2)

LC50 - Fish [1]	≥ 1000 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	21100 – 25900 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea:
ErC50 algae	> 1000 mg/l (7 day(s), Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

##### 1-butanol (71-36-3)

LC50 - Fish [1]	1376 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	1328 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	225 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

#### 12.2. Persistence and degradability

##### Propylene Glycol Methyl Ether (107-98-2)

Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
ThOD	1.95 g O <sub>2</sub> /g substance

##### 1-butanol (71-36-3)

Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.1 – 1.92 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.46 g O <sub>2</sub> /g substance
ThOD	2.59 g O <sub>2</sub> /g substance

#### 12.3. Bioaccumulative potential

##### Propylene Glycol Methyl Ether (107-98-2)

Partition coefficient n-octanol/water (Log Pow)	< 1 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

##### Stoddard solvent (8052-41-3)

Partition coefficient n-octanol/water (Log Pow)	3.16 – 7.06
---	-------------

##### 1-butanol (71-36-3)

Partition coefficient n-octanol/water (Log Pow)	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).



# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.4. Mobility in soil

#### Propylene Glycol Methyl Ether (107-98-2)

Surface tension	70.7 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.152 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

#### Stoddard solvent (8052-41-3)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.85 – 6.74 (log Koc)
--	-----------------------

#### 1-butanol (71-36-3)

Surface tension	69.9 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.54 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil. May be harmful to plant growth, blooming and fruit formation.

### 12.5. Other adverse effects

No additional information available




## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
 Additional information : Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
1263	Not applicable	1263	1263
<b>14.2. Proper Shipping Name</b>			
Paint related material	Not applicable	PAINT RELATED MATERIAL	Paint related material
<b>14.3. Transport hazard class(es)</b>			
3	Not applicable	3	3
 Not applicable			
<b>14.4. Packing group</b>			
II	Not applicable	II	II

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	IATA
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: No	Not applicable	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

### 14.6. Special precautions for user

**DOT**

UN-No.(DOT)

: UN1263

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons). 367 - For the purposes of documentation and package marking: a. The proper shipping name "Paint related material" may be used for consignments of packages containing "Paint" and "Paint related material" in the same package; b. The proper shipping name "Paint related material, corrosive, flammable" may be used for consignments of packages containing "Paint, corrosive, flammable" and "Paint related material, corrosive, flammable" in the same package; c. The proper shipping name "Paint related material, flammable, corrosive" may be used for consignments of packages containing "Paint, flammable, corrosive" and "Paint related material, flammable, corrosive" in the same package; and d. The proper shipping name "Printing ink related material" may be used for consignments of packages containing "Printing ink" and "Printing ink related material" in the same package. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. B131 - When transported by highway, rail, or cargo vessel, waste Paint and Paint related material (UN1263; PG II and PG III), when in plastic or metal inner packagings of not more than 26.5 L (7 gallons), are excepted from the marking requirements in §172.301(a) and (c) and the labeling requirements in §172.400(a), when further packed in the following specification and non-specification bulk outer packagings and under the following conditions:  a. Primary receptacles must conform to the general packaging requirements of subpart B of part 173 of this subchapter and may not leak. If they do leak, they must be overpacked in packagings conforming to the specification requirements of part 178 of this subchapter or in salvage packagings conforming to the requirements in §173.12 of this subchapter.  b. Primary receptacles must be further packed in non-specification bulk outer packagings such as cubic yard boxes, plastic rigid-wall bulk containers, dump trailers, and roll-off containers. Bulk outer packagings must be liquid tight through design or by the use of lining materials.  c. Primary receptacles may also be further packed in specification bulk outer packagings. Authorized specification bulk outer packagings are UN11G fiberboard intermediate bulk containers (IBC) and UN13H4 woven plastic, coated and with liner flexible intermediate bulk containers (FIBCs) meeting the Packing Group II performance level and lined with a plastic liner of at least 6 mil thickness.  d. All inner packagings placed inside bulk outer packagings must be blocked and braced to prevent movement during transportation that could cause the container to open or fall over. Specification IBCs and FIBCs are to be secured to a pallet. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F). TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 173
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

### TDG

Emergency Response Guide (ERG) Number : 128

### IMDG

Special provision (IMDG) : 163, 367  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
Packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP8, TP28  
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS  
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER  
Stowage category (IMDG) : B  
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

### IATA

PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L  
Special provision (IATA) : A3, A72, A192  
ERG code (IATA) : 3L

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Methyl Ethyl Ketone	CAS-No. 78-93-3	25 – 50%
Stoddard solvent	CAS-No. 8052-41-3	0.1 – 0.5%
1-butanol	CAS-No. 71-36-3	1 – 5%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

toluene	CAS-No. 108-88-3	15 – 25%
---------	------------------	----------

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1000 lb
-----------	---------

### 15.2. International regulations

#### CANADA

### toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

### Propylene Glycol Methyl Ether (107-98-2)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

### toluene (108-88-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Propylene Glycol Methyl Ether (107-98-2)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. US State regulations

#### **WARNING:**

This product can expose you to 4,4'-isopropylidenediphenol; bisphenol A, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Full text of H-phrases

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

# Poxylube #800 PTFE Coating - Heat Curing - Clear

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), USA

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, WE MAKE NO WARRANTY, EXPRESSED, OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.