



EASY CLEAN

DEGREASER / CLEANER: AIR DRY

SERIES D158

CONCENTRATED, WATER REDUCIBLE



PORT BYRON, IL 61275 • 1-309-523-2121

1-800-747-1084 • FAX: 1-309-523-3912

www.sandstromproducts.com

DESCRIPTION

Easy Clean is a pleasant smelling, highly concentrated cleaner and degreaser. Use this product to remove grease, fats, dirt and grime from flooring and other surfaces to maintain cleanliness or prepare for surface etching.

TYPICAL USES

- Degreaser on masonry or concrete floors or walls prior to surface etching (see Sandstrom Easy Etch, C150) for coating adhesion
- Cleaning solution for regular maintenance of shop floors, garages, etc.

NOTICE

Before using this product, read all warnings, limitations and safety information printed on the product label, Safety Data Sheet (MSDS) and Technical Data Sheet.

LIMITATIONS

- Do not use on surfaces that may contact food.
- Do not use on uncoated steel.

COMPOSITION AND PHYSICAL PROPERTIES

Net Weight per gallon	8.3 – 8.5 lbs./gallon	Shelf Life	24 Months from Date of Shipment in unopened container
Weight Solids	25% (Theoretical)	Storage Conditions	40°F to 120°F
VOC	3.45 lbs./gallon	Freeze/Thaw Stability	Stable, as supplied
Odor	Citrus	Flash Point	387°F (Theoretical)
Mix Ratio <i>Water : Easy Clean</i>	Coated or Tiled Floor	50:1	Coverage Rate* 100 sq. ft./ reduced Easy Clean gallon (10:1)
	Oily Concrete	10:1	
	Saturated Concrete	1:1	

*Actual figures will vary depending on condition of surface and mix ratio.

SURFACE PREPARATION

Remove all thick deposits of grease, grime and dirt with a scraper, chisel, shot blaster or other removal tool.

MIXING

Mix well before thinning.

THINNING

See Mix Ratio above for suggested dilution rates of Easy Clean with water.

DANGER! USE WITH ADEQUATE VENTILATION.

APPLICATION

Dilute with water according to the Mix Ratio suggested above. Pour mixed solution over 10' x 10' area. Agitate with stiff bristled brush in a brisk circular motion or use a power scrubber to loosen grease, grime and dirt.

Rinse with pressurized clean water.

Repeat process until no suds or oily residue remains.

If preparing surface for coating adhesion, apply Sandstrom Easy Etch (Sandstrom C150) per container instructions. Surface does not need to be dry before application of Easy Etch.

CLEANUP

Rinse tools and surfaces with water until rinse water runs clear of suds.

IMPORTANT NOTICE TO BUYER / WARRANTY AND LIMITATIONS ON OUR LIABILITY

We warrant our products to be free of manufacturing defects and that they meet our current published physical properties and specifications. All information and suggestions presented are rendered gratis and are accurate to the best of our knowledge. They are based on technical data we believe to be reliable and are intended for use by persons having skill and "know-how" at their own discretion and risk. Prior to use, customers are cautioned to determine the suitability of our products for any given application through their own testing. **NO WARRANTY IS MADE, EXPRESS OR IMPLIED, REGARDING SUCH INFORMATION, THE DATA ON WHICH IT IS BASED OR THE RESULTS OBTAINED FROM ITS USE OR THAT OUR PRODUCT SHALL BE MERCHANTABLE OR FIT FOR ANY PARTICULAR PURPOSE. SUCH STATEMENTS ARE NOT INTENDED TO SUGGEST INFRINGEMENT OF ANY PATENT.** Since conditions of use of our products are beyond our control, all suggestions and statements are made without guarantee, warranty or other responsibility, express or implied, on our part. We assume no responsibility for results obtained, or damages incurred, from their use beyond replacing material proved to be defective or refunding the purchase price of such material at our option. Acceptance of delivery of our product means you have accepted the terms of this warranty, whether or not purchase orders of other documents state terms that vary from this warning. No seller is authorized to make any representations or warranty or assume any other liability on our behalf with any sales of our products. SANDSTROM PRODUCTS COMPANY